

EM500-SMT

Soil Moisture Sensor



EM500-SMT is designed for measuring soil moisture in harsh environments and transmitting data using LoRaWAN[®] technology. With this low power consumption technology, EM500-SMT can work up to 10 years with 19000 mAh battery. Combining with Milesight LoRaWAN[®] gateway and Milesight IoT Cloud solution, users can manage all sensor data remotely and visually.

EM500-SMT is widely used for outdoor applications like smart agriculture, smart horticulture, etc.

Features

- > High precision for multiple kinds of soil
- > Ultra-wide-distance transmission up to line of sight of 10km
- > IP66 waterproof enclosure for harsh environment applications
- Built-in 19000 mAh replaceable battery and work for 10 years without replacement
- > Equipped with NFC for easy configuration
- Compliant with standard LoRaWAN[®] gateways and network servers
- > Quick and easy management with Milesight IoT Cloud solution

Applications

- Irrigation Control
- Greenhouse control
- > Smart agriculture
- Smart horticulture
- Golf course maintenance

Specifications

Wireless Transmission	
Technology	LoRaWAN [®]
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-147dBm @300bps
Mode	OTAA/ABP Class A
Measurement	
Range	0% to 100% RH
Accuracy	±2%
Resolution	0.5%
Operation	
Power On & Off	NFC, power button (Internal)
Configuration	Mobile APP(via NFC) or PC software(via USB Type-C)
Physical Characteristic	S
Cable Length	5 m
Power Supply	19000 mAh Li-SOCL ₂ battery (ER34615)
Battery Life*	5 years (10 min interval, SF12)
	>10 years (10 min interval, SF7)
Operating Temperature	-30°C to +60°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	IP66
Dimension	Transceiver: 105.4 × 71 × 69.5 mm (4.1 × 2.8 × 2.7 in)
	Soil Sensor: 89 × 18 × 7 mm (3.5 × 0.7 × 0.3 in)
	(Probe length: 50mm/1.97 in)
Installation	Pole, wall or DIN Rail Mounting

* Tested under laboratory conditions and for guideline purposes only.

