

## **AXIS Camera Station S2224 Appliance** All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2224 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2224 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 24 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2224 provides a reliable surveillance solution.

- > All-in-one solution with integrated PoE switch
- > High-definition surveillance with up to 4K resolution
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products



## **AXIS Camera Station S2224 Appliance**

Licenses	24 AXIS Camera Station core licenses included, can be upgraded with additional licenses (sold separately)		Up to 24 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 24 video channels and 48 doors		
Hardware		Recording	Qualified for recording up to 24 video channels with a total
Processor	Intel® Core™ i5	incestung	recording rate up to 384 Mbit per second
Memory	8 GB	General	
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 12 TB (2x6 TB)	Operating system	Microsoft <sup>®</sup> Windows <sup>®</sup> 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD
RAID	RAID levels: 0, 1, 10	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
Switch	24 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Graphic card	Intel® HD Graphics	EN 6100 FCC Part KC KN35 Safety IEC/EN 6	CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Power	Max 520 W, 260 W PoE dedicated 100 - 240 V AC, 6.5-2.5 A, 50/60 Hz		
Connectors	Front side: 1× USB 3.0 1× Audio line in 1× Audio line out Rear side Switch: 24× PoE ports 10/100 Mbps 1× SFP 10/100/1000 Mbps 1× RJ45 10/100/1000 Mbps Rear side Server: 1× RJ45 10/100/1000 Mbps 2× USB 2.0 1 Displayport™ 1 HDMI port		
		Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis
		Weight	11 kg (24.3 lb)
		Included accessories	Rack rails, power cord
		Optional accessories	Surveillance Hard Drive 6 TB available from Axis Axis desktop terminals Axis Ethernet surge protector
Video			For more accessories, see axis.com
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p	Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty

## **AXIS Camera Station**

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility: axis.com/environmental-responsibility

